


# 57BYGN

# HYBRID STEPPING MOTOR



## General Specifications



Step Accuracy	± 5%
Temperature Rise	80 °C Max
Insulation Resistance	100MΩ Min.500VC DC
Ambient Temperature	-20°C~+50°C
Dielectric Strength	500VAC 1 minute
Max Radial Force	75N (20mm from front flange)
Max Axial Force	15N

## Technical Specifications

Model	Step Angle (°/Step)	Lead Wire (NO.)	Voltage (V)	Current (A/Phase)	Resistance (Ω/Phase)	Inductance (mH/Phase)	Holding Torque (Kg.cm)	Motor Height L (mm)	Motor Weight (Kg)
57BYGN001	1.8	6	12	0.38	32	25	3.0	41	0.45
57BYGN027		4	2.8	1.4	2.1	3.5	3.9	41	0.45
57BYGN200-19A		6	5	1.0	5.0	11.5	5.8	51	0.65
57BYGN204		6	11.2	0.4	28	30	3.8	51	0.65
57BYGN400-11A		4	5.5	1.1	5.0	12	7.8	56	0.70
57BYGN412		4	4.4	2.0	2.2	6.3	9.0	56	0.70

\* Products can be customized by special request.

## Wiring Diagram



## Mechanical Dimension

